

PRASAD INTERNATIONAL PVT. LTD.,







REACH Status: Pre Registered


Date : 01.01.2018 Revision: 04

| D | | D | |
|------|------|-----------|--------|
| Proc | THIF | Descri | Intion |
| | auct | D C 3 C I | |

| CI Generic Name | Pigment Red 48:3 | PIL Product Code | PRPL 1024 |
|-------------------|------------------|------------------|------------|
| CI No. | 15865:3 | CAS No. | 15782-05-5 |
| EINECS No. | 239-879-2 | Chemical Type | BONA, Sr |
| Molecular Formula | C18H13CLN2O6S-Sr | Molecular Weight | 508 |

Chemical Name: 2-Naphthalenecarboxylic acid , 4-[(5-chloro - 4- methyl -2-sulfophenyl)azo] - 3- hydroxy - , STRONTIUM salt (1:1)

| Physical Properties | | |
|---------------------------|-------------|--|
| Sieve Residue (PPM) Max. | 1000 | |
| Oil Absorption(gms) | 60 - 75 | |
| Bulk Density(gm/ml) | 0.15 – 0.30 | |
| Salt Content (%) Max. | 1 | |
| Moisture Content (%) Max. | 1 | |
| PH Value | 7.0 – 8.5 | |



| Fastness properties | | | | |
|---------------------|--------------|----------------|--|--|
| Heat °C | PP-Mass Tone | 240°C / 5 min. | | |
| Heat °C | PP-Tint Tone | 220°C / 5 min. | | |
| Light | Mass Tone | 6 | | |
| Light | Tint Tone | 4 | | |
| Weather | Mass Tone | - | | |
| Weather | Tint Tone | - | | |
| Migration | | 5 | | |

| Specification | | | | |
|------------------------------|--|--|--|--|
| Coloristic properties (Tint) | Strength: ±5% | | | |
| Coloristic properties (Tint) | DA,DB,DE,DC,DH,DL: ± 1 | | | |
| Light fastness: Scale 1-8 | 1~Poor & 8 ~ Excellent | | | |
| Weather fastness : Scale 1-5 | 1~Poor & 5 ~ Excellent | | | |
| Migration : Scale 1-5 | 1~Poor & 5 ~ Excellent | | | |
| Heat Stability °C | DE ≤3 at Maximum Temp. With dwell time 5 minutes. | | | |

Application

Plasticized & rigid PVC, LDPE, LLDPE, PP, HDPE, Rubber, ABS, spin dyeing, PS, PU

Note

The colors above have been generated electronically and should therefore not be used for comparison purposes. The colors are meant to give a first impression of the colorant shade.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our Product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

Regd. Office: 601-602, Surya Rath, Panchvati, 1st. Lane, Opp. White House, Ambawadi, Ahmedabad-380 006, Gujarat, India **Phone:** +91-79-26422349/26425650 **Fax:** +91-79-26562870 **E-mail:** techservices@prasadinternational.com